





Fitted with	LED - Energy efficiency category A+
Illuminance 100 cm	130 000 lx
Colour rendering index (Ra)	> 96
Work equipment	Electronic converter
Voltage	100-240 V; 50/60 Hz
Mains lead	Direct power supply
Luminaire body	Polyamid (PA)
Weight (net)	20 kg
Power consumption	40 W
Usage	Keypad at cardanic
Balance of articulation joints	Spring
Class of protection	I
Accessory	Sterilizable handle, handle cover
Norms	EN 60601-1, EN 60601-2-41
Special features	Dimmable, focusable, colour changeable, sterilizable handle
Fastening	Rolling stand
System of protection	IP 20 according to IEC 60529 luminaire head IP 43 (horizontal position)
Medical device class	I according to MDR

	lighting field / 1,0 m changeable value 16 / 20 / 25 cm	Colour temperature changeable value 3700K / 4300K / 4700K	Dimmable	Order No.
TRIANGO Fokus 130-3 F SCHUKO	X	X	X	D16.292.000
TRIANGO Fokus 130-3 F US-HG	X	X	X	D16.294.000
TRIANGO Fokus 130-3 F CH	X	X	X	D16.295.000
TRIANGO Fokus 130-3 F UK	X	X	X	D16.293.000
TRIANGO Fokus 130-3 F AUS	X	X	X	D16.296.000

Light distribution



Technical drawing

