





<b>Fitted with</b>	LED - Energy efficiency category A+
<b>Illuminance 100 cm</b>	130 000 lx
<b>Colour rendering index (Ra)</b>	> 96
<b>Work equipment</b>	Electronic converter
<b>Voltage</b>	100-240 V; 50/60 Hz
<b>Mains lead</b>	Direct power supply
<b>Luminaire body</b>	Polyamid (PA)
<b>Weight (net)</b>	15,3 kg
<b>Power consumption</b>	40 W
<b>Usage</b>	Keypad at cardanic
<b>Balance of articulation joints</b>	Spring
<b>Class of protection</b>	I
<b>Accessory</b>	Sterilizable handle, handle cover
<b>Norms</b>	EN 60601-1, EN 60601-2-41
<b>Special features</b>	Dimmable, focusable, colour changeable, sterilizable handle
<b>Fastening</b>	Wall mount
<b>System of protection</b>	IP 20 according to IEC 60529 luminaire head IP 43 (horizontal position)
<b>Medical device class</b>	I according to MDR

	lighting field / 1,0 m	Colour temperature	Dimmable	Order No.
	changeable value 16 / 20 / 25 cm	changeable value 3700K / 4300K / 4700K		
TRIANGO Fokus 130-3 W	X	X	X	D16.291.000
TRIANGO Fokus 130-3 W US-HG	X	X	X	D16.298.000

Light distribution



Technical drawing

